

TL-6500 Auto Lensmeter



Green measurement light
Hartmann sensor
7.0 inch touch screen
uv testing

Features




7.0 inch tiltable LCD screen, provides comfortable operation for both standing and sitting operators




Hartmann sensor with 108 measurement points, which provides easier and faster measurements



Icon-based interface, provides easier and convenient operation




High efficient progressive lens measurement



Dark sunglasses measurement


Automatic identification the single vision lens and progressive lens



Virtual PD measurement interface



High quality ink provides more clearly marker.



Data transmission with CV-7600 Computerized vision tester

TL-6500 Specifications		
Measurement range	Sphere	-25.00 to +25.00 D (Step: 0.01 / 0.06 / 0.12 / 0.25 D)
	Cylinder	0 to ±10.00 D (Step: 0.01 / 0.06 / 0.12 / 0.25 D)
	Axis	0 to 180° (Step: 1°)
	ADD	0 to +10.00 D (Step: 0.01 / 0.06 / 0.12 / 0.25 D)
	Prism	0 to 20 Δ (0.01 / 0.06 / 0.12 / 0.25 Δ)
Measurement mode	Measurable lens diameter	φ 10 to 90 mm
	Cylinder	-, MIX, +
PD measurement	Prism	X-Y, P-R
	Wavelength / Measuring point	20.0 to 45.0mm (monocular), Single vision PD, Progressive lens far vision PD
Display	Wavelength / Measuring point	535 nm (green) / 108 within nosepiece
Marking system	Display	7.0 inch color LCD
Printer	Marking system	Ink cartridge type
Interface	Printer	Build-in thermal printer (Optional)
Dimensions	Interface	RS232/ Bluetooth
Weight	Dimensions	255 (W) x 224 (D) x 434 (H) mm
Power Supply	Weight	5.0kg
Power consumption:	Power Supply	AC 100 to 240 V, 50 / 60 Hz
	Power consumption:	35w maxium